

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number
WO 03/089728 A1

(51) International Patent Classification⁷: **E04B 1/30**

(21) International Application Number: PCT/KR03/00643

(22) International Filing Date: 31 March 2003 (31.03.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2002-0021093 18 April 2002 (18.04.2002) KR

(71) Applicant and

(72) Inventor: HAN, Bong-Kil [KR/KR]; 2 Fl., 75-9, Sadang-Dong, Tongjak-Ku, Seoul 156-090 (KR).

(74) Agent: PARK, Jong-Man; Tomorrow Int'l Patent & Law firm, 2th Floor, Kumma Building, 827-24, Yoksam-dong, Kangnam-Ku, Seoul 135-080 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONSTRUCTION METHOD FOR SRC STRUCTURED HIGH RISE BUILDING



(57) Abstract: This invention provides a method for constructing a high rise building having a core and a residence space around the core, the method including the steps of: (a) installing a steel-frame pillar on a shaft portion of the core; (b) connecting a girder to the steel-frame pillar, the girder includes an anchor-connecting member to which a steel-frame beam is connected, a portion of the anchor-connecting member being buried in a core wall; (c) assembling the steel-frame beam on the anchor-connecting member; (d) arranging reinforcing bars in a deck plate or a slab type mold installed on the steel-frame beam, and in the core wall; and (e) applying a slab concrete and a core concrete simultaneously or in this order. According to the present method, the quality of the core and slab structure is improved, while providing the construction safety and saving the construction costs.

SPECIFICATION

【Title of the Invention】

CONSTRUCTION METHOD FOR SRC STRUCTURED HIGH RISE
BUILDING

5

【Technical Field】

The present invention relates to a method for constructing a high rise building, which has residence spaces in and around a core, using a steel-framed reinforced concrete construction, and more particularly, to a method for
10 constructing a high rise building structure that can improve quality of a slab and a core construction as well as construction efficiency and stability and reduces the construction costs by firstly mounting steel-frames for a core and a slab in advance and then applying reinforced concrete for the slab and the core.

15 【Background Arts】

Generally, a reinforced concrete (RC) construction, a steel-frame (S) construction, and a steel-framed reinforced concrete (SRC) construction are typically used to construct buildings. In recent years, as the buildings are large-sized and high-storied, a combination of three constructions has been widely used.

Furthermore, as the buildings are large-sized and high-storied, an earthquake-resistance and wind-resistance design becomes a major issue when constructing the buildings. Therefore, a core portion in which facilities such as an elevator, electric facility, system facility and a staircase are arranged is firstly
5 constructed using the reinforced concrete construction, after which a main pillar portion for defining residence spaces is secondly constructed using the steel-frame construction.

FIGS. 1 and 2 show a conventional method for constructing a building having the SRC structure in which a core is constructed in advance.

10 In the drawings, the reference numeral 1 indicates a building core. The core 1 is constructed in advance using the RC construction considering the wind-resistance. Generally, a tower crane is installed in a core 1, and core dedicated facilities such as a hoist and a concrete distributor are installed an outer side of the core 1. A reinforcing bar 3 is arranged by the core-dedicated facilities, and a
15 concrete 5 is applied to build the core in advance.

At this point, an anchor member 7 is installed when the concrete 5 is applied to prepare the construction of the steel-frame structure. The anchor member 7 includes a connecting member 7a buried in the concrete 5, an anchor plate 7b welded on the connecting member 7a, and a gusset plate 7c welded on

the anchor plate 7b.

After the above, a steel-frame beam 9 is assembled on the gusset plate 7c using high tension bolts 7c, after which a slab 11 is built by installing a slab type mold, arranging reinforcing bars and applying concrete to a slab mold.

5 However, in the conventional method for constructing a building using the SRC construction in which the core is firstly build in advance, many dedicated facilities such as the hoist and the concrete distributor are required to arrange the reinforcing bar and apply the concrete. The dedicated facilities should be removed for the construction of the slab, complicating the construction process
10 and increasing the construction costs.

In addition, since the advanced core has a small size than that of the residence space defined by the slab, which will be constructed after the core, it is difficult to manage the manpower, manual tool and equipments. Furthermore, the core and the slab should be constructed by separately applying concrete, a
15 reinforcing bar connecting the core to the slab have to be installed on walls in advance, thereby further increasing the construction costs. The separate application of the concrete is apt to deteriorate the quality of the buildings.

In addition, since the working processes for the core and the slab should be done remotely in a vertical direction, the construction process is complicated

and the quality control is difficult.

Particularly, since there is no approaching path to the anchor member for installing the steel-frame, a safety rail should be installed on each of the members to install the steel-frame beam. As a result, the construction period is longer, and
5 the construction costs are inevitably higher.

【Summary of the Invention】

Therefore, the present invention has been made in an effort to solve the above-described problems of the conventional arts.

10 It is an objective of the present invention to provide to a method for constructing a high rise building structure that can improve quality of a slab as well as construction efficiency and stability and reduces the construction costs by firstly mounting steel-frames for a core and a slab in advance and then secondly
applying reinforced concretes for the slab and the core simultaneously or in this
15 order.

To achieve the above objectives, the present invention provides a method for constructing a high rise building having a core and a residence space around the core, the method comprising the steps of (a) installing a steel-frame pillar on a shaft portion of the core; (b) installing a girder to the steel-frame pillar, the girder

includes an anchor-connecting member to which a steel-frame beam is connected, a portion of the anchor-connecting member being buried in a core wall; (c) assembling the steel-frame beam on the anchor-connecting member; (d) arranging reinforcing bars in a deck plate or a slab type mold installed on the steel-frame beam, and in the core wall; and (e) applying a slab concrete and a core concrete simultaneously or in this order.

Preferably, the anchor-connecting member comprises a connecting member connected to the girder by welding or bolts, an anchor plate connected to the connecting member by welding or bolts, a gusset plate welded on the anchor plate, and a stud or shear connector extended from the anchor plate to the concrete wall and buried in the concrete.

Further preferably, the step (c) further comprises the steps of forming a slot hole on the anchor-connecting member and coupling a high tension bolt in the slot hole to be assembled on the steel-frame beam.

Still further preferably, plural sub-connecting members for supporting the deck plate or the slab type mold are installed on the girder installed between the steel-frame pillars, the sub-connecting members including a connecting member coupled to the girder and a supporting member coupled to one end of the connecting member.

【Brief Description of the Drawings】

FIG. 1 is a perspective view illustrating a conventional constructing structure of a high-rise building;

FIG. 2 is a sectional view of a conventional steel-frame beam structure;

5 FIG. 3 is a perspective view illustrating a constructing structure of a high-rise building according to a preferred embodiment of the present invention;

FIG. 4 is a sectional view of a girder and steel-frame beam structures according to a preferred embodiment of the present invention; and

10 FIG. 5 is a sectional view of a slab installing structure according to a preferred embodiment of the present invention.

【Embodiments】

The present invention will be described more in detail with reference to the accompanying drawings.

15 FIG. 3 shows a perspective view illustrating a constructing structure of a high rise building according to a preferred embodiment of the present invention, and FIG. 4 shows a sectional view of a girder and steel-frame beam structures according to a preferred embodiment of the present invention.

As shown in the drawings, a high rise building is constructed by firstly

installing a steel-frame pillar 23 on a shaft portion of a core 21, and is then secondly a girder 25 and a steel-frame beam 31 are installed on the steel-frame pillar 23. Then, reinforcing bars for a slab 33 and a core 21 are arranged and concretes are applied. At this point, after the reinforcing bars are arranged, the
5 concrete may be firstly applied on the slab 33, and then may be applied on the core 21.

In the present invention, an anchor-connecting member 27 and a sub-connecting member 34 are integrated with the girder 25 by welding or bolts before the construction.

10 The anchor-connecting member 27 is installed on a core shaft portion to support the steel-frame beam 31. The anchor-connecting member 27 includes a connecting member 27a connected to the girder 25 by welding or bolts, an anchor plate 27b connected to the connecting member 27a by welding or bolts, a gusset plate 27c welded on the anchor plate 27b, and a stud or shear connector 27d
15 extended from the anchor plate 27b to the inside of the concrete wall 21a and buried in the concrete.

The gusset plate 27c is provided with a slot hole 27g to compensate for the coupling error with the steel-frame beam 31.

The sub-connecting member 34 is provided to support the deck plate 33b

for installing the slab 33. The sub-connecting member 34 includes a connecting member 34a connected to the girder 25 by welding or bolts and a supporting member 34b connected to one end of the connecting member 34a by welding or a bolt. A plurality of sub-connecting members 34 may be provided.

5 The construction method of a building according to the present invention will be described hereinafter with reference to the accompanying drawings.

 The steel-frame pillar 23 is first installed on the shaft portion of the core 21, and a horizontal girder 25 is connected to the steel-frame pillar 23. Then, the steel-frame beam 31 is assembled on the girder 25 using the anchor-connecting
10 member 27, thereby completing the steel-frame construction process.

 At this point, a high tension bolt 27f coupled on the slot hole 27g formed on the gusset plate 27c of the anchor-connecting member 27 is strongly connected to the steel-frame beam 31. The high tensioned bolt 27f can be adjusted along the slot hole 27g to compensate for the assembling error.

15 After the above, a reinforcing bar 21b is mounted on a wall of the core 21, and the deck plate 33b or a slab type mold is installed on the steel-frame beam 31 and the girder 25 using the sub-connecting member 34, after which the reinforcing bar is installed in the deck plate 33b or the slab type mold.

 Then, system forms are mounted on the shaft portion of the core 21, and

euro-form or conventional form is installed on a living section, after which concretes 21a and 33a for a core wall and a slab are applied simultaneously. Alternatively, the concrete for the slab may be firstly applied and is then secondary the concrete for the core wall may be applied.

5

【Industrial Applicability】

As described above, as steel-frame for the core and the slab are firstly constructed, and is then reinforcing bars are arranged in the core and slab sections, after which the concretes are applied to the slab and core sections simultaneously or in this order, the quality of the core and slab structures is improved, while providing the construction safety and saving the construction costs.

Furthermore, since the core and slab concrete constructions are performed after the steel-frame construction, the working balance of a finishing process such as an exterior wall curtain construction and an interior finishing construction can be controlled with the core and slab constructions, thereby reducing the construction period.

【Claims】

1. A method for constructing a high rise building having a core and a residence space around the core, the method comprising the steps of:

(a) installing a steel-frame pillar on a shaft portion of the core;

5 (b) connecting a girder to the steel-frame pillar, the girder includes an anchor-connecting member to which a steel-frame beam is connected, a portion of the anchor-connecting member being buried in a core wall;

(c) assembling the steel-frame beam on the anchor-connecting member;

(d) arranging reinforcing bars in a deck plate or a slab type mold installed
10 on the steel-frame beam, and in the core wall; and

(e) applying a slab concrete and a core concrete simultaneously or in this order.

2. The method of claim 1 wherein plural sub-connecting members for supporting the deck plate or the slab type mold are installed on the girder installed
15 between the steel-frame pillars, the sub-connecting members including a connecting member coupled to the girder and a supporting member coupled to one end of the connecting member.


3. The method of claim 1 wherein the anchor-connecting member comprises a connecting member connected to the girder by welding or bolts, an

anchor plate connected to the connecting member by welding or bolts, a gusset plate welded on the anchor plate, and a stud or shear connector extended from the anchor plate to the concrete wall and buried in the concrete.

4. The method of claim 1 wherein the step (c) further comprises the steps
- 5 of forming a slot hole on the anchor-connecting member and coupling a high tensioned bolt in the slot hole to be assembled on the steel-frame beam.


1/4

Fig. 1




2/4

Fig. 2



3/4

Fig. 3



4/4

Fig. 4





Fig. 5



INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR03/00643**A. CLASSIFICATION OF SUBJECT MATTER****IPC7 E04B 1/30**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7 E04B 1/30, 1/24

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

KR, JP : IPC7 E04B 1/30, 1/24

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 05-171684 A (KAJIMA CORP) 9 JULY 1993	1
A	JP 04-306335 A (NAKAGAWA ATSUSHI) 29 OCTOBER 1992	1
A	JP 06-264503 A (ASAHI CHEM IND CO LTD) 20 SEPTEMBER 1994	1

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family


Date of the actual completion of the international search

22 AUGUST 2003 (22.08.2003)

Date of mailing of the international search report

25 AUGUST 2003 (25.08.2003)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office
920 Dunsan-dong, Seo-gu, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

LIM, Jung Seok

Telephone No. 82-42-481-5803

